



SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

Thurmalox 837B

Product Code(s) : 837B

Recommended use of the chemical and restrictions on use

: High Temperature Primer

Use pattern: Professional Use Only Recommended restrictions: None Known.

Chemical family : Mixture.

Name, address, and telephone number of the supplier:

Name, address, and telephone number of the manufacturer:

Dampney Company, Inc. Refer to supplier

85 Paris Street

Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com

Supplier's Telephone # : (617) 389-2805

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.).

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Cloudy liquid. Solvent odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Flammable Liquid – Category 2

Skin Irritant – Category 2

Eye irritant – Category 2

Eye Damage – Category 1

Specific Target Organ Toxicity Single Exposure – Category 3

Aquatic Chronic – Category 2

GHS-02 Flame

GHS-05 Corrosion

GHS-07 Exclamation Mark



DANGER!

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

PREVENTION:

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting, mixing, application equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust, fume, gas, mist, vapours, or spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, eye protection, and face protection.

RESPONSE:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.



SAFETY DATA SHEET

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER, doctor, or hospital emergency room.
P312 Call a POISON CENTER, doctor, or hospital emergency room if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry chemical, CO₂, water spray (fog) or foam to extinguish.

STORAGE:

P403 + P233 + P235 (S) Store in a cool, well-ventilated place. Keep container tightly closed.
P405 Store locked up.

DISPOSAL:

P501 Dispose of contents and empty container in accordance with local, state and federal regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS #	Concentration (% by weight)
Para-Chlorobenzotrifluoride	98-56-6	40.0 – 50.0
1-Methoxy-2-Propanol Acetate	108-65-6	5.0 – 10.0
Ethanol	64-17-5	0.1 – 5.0
Isobutanol	78-83-1	0.1 - 5.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion : IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Inhalation :IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact :IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Eye contact :In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediately call a POISON CENTER, doctor, or hospital emergency room.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media: Do not use water jet, as this may spread burning material.

Special hazards arising from the substance or mixture / Conditions of flammability

Highly flammable liquid and vapor. Keep away from heat and flame. This product will accumulate static charge by flow, splashing or agitation. Vapors may travel considerable distance to a source of ignition and flash back. Vapours are heavier than air and collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

: Flammable Liquids - Category 2

Hazardous combustion products: Carbon oxides ; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters



SAFETY DATA SHEET

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures: Move containers from fire area if safe to do so. Use water spray to cool unopened containers. Avoid spreading burning liquid with water spray used for cooling purposes. Do not allow run-off from fire fighting to enter drains or water courses. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Environmental precautions: Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapour or mist. Restrict access to area until completion of clean-up. Remove all sources of ignition. All persons dealing with the clean-up should wear the appropriate personal protective equipment. For personal protection see section 8. Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Contaminated absorbent material may pose the same hazards as the spilled product. Pick up and transfer to properly labelled containers. Contact the proper local authorities.

Special spill response procedures: In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat and flame. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Bond and ground transfer containers and equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Avoid breathing vapour or mist. Do not ingest. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials. Encourage good housekeeping and personal hygiene.

Conditions for safe storage: Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Take measures to prevent the build up of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials: Strong oxidizers.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

Chemical Name	CAS	OSHA TWA	OSHA PEL	OSHA STEL
Para-Chlorobenzotrifluoride	98-56-6	None	None	None
1-Methoxy-2-Propanol Acetate	108-65-6	50 ppm	N/Av	N/Av
Ethanol	64-17-5	1000 ppm	1000 ppm 1900 mg/m3	1000 ppm
Isobutanol	78-83-1	50 ppm	100 ppm 300 mg/m3	50 ppm

Exposure controls

Ventilation and engineering measures: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection: If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection: Wear protective gloves. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection: Chemical splash goggles are recommended.



SAFETY DATA SHEET

Other protective equipment : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations : Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odour	: Clear liquid. Solvent odor.
Odour threshold	: N/A
pH	: N/A
Melting/Freezing point	: N/A
Boiling range	: 172.4°F – 302.0°F
Flash point	: 109.0°F – 116.0°F
Evaporation rate (BuAe = 1)	: 0.38 times slower than n-Butyl Acetate.
Vapour pressure Vapour density	: Heavier than air
Relative density / Specific gravity	: 1.25222
% Volatile by Weight	: 53.44%
Weight per Gallon	: 10.4 lb/gal
VOC	: 2.06 lbs / gal

SECTION 10. STABILITY AND REACTIVITY

Incompatibility:

avoid contact with strong oxidizing agents, acids or bases.

Conditions to avoid:

avoid heat, open flames.

Hazardous decomposition products:

carbon monoxide and unidentified organics may be formed.

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects:

PARA-CHLOROBENZOTRIFLUORIDE

Inhalation	Rat	LC50 20000. mg/M3
Oral	Rat	LD50 13000. mg/kg
Skin	Rabbit	LD50 2700. mg/kg

1-METHOXY-2-PROPANOL ACETATE

Inhalation	Rat	LC50 4 HOURS 5344. PPM
Oral	Rat	LD50 8532. mg/kg
Skin	Rabbit	LD50 5000. mg/kg

ETHANOL

Inhalation	Rat	LC50 20000. PPM
Oral	Rat	LD50 7060. mg/kg

ISOBUTANOL

Inhalation	Rat	LC50 8000. PPM
Oral	Rat	LD50 2500. mg/kg
Skin	Rabbit	LD50 4240. mg/kg

Specific target organ effects: Eyes, skin, respiratory system, digestive system, central nervous system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Toxicological data :

There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data. See below for individual ingredient acute toxicity data.

Other important toxicological hazards

: None known or reported by the manufacturer.



SAFETY DATA SHEET

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Contains material that may be harmful in the environment. Should not be released into the environment. See the following tables for the substance's ecotoxicity data.

Ecotoxicity data:

Ingredients	CAS No		
Para-Chlorobenzotrifluoride	98-56-6	Toxicity to fish	EC50 Danio rerio (Zebra fish) 3 mg/l / 96hrs
		Toxicity to Algae	EC50 Pseudokirchneriella subcapitata (green algae) 0.41 mg/l 72 hrs
1-Methoxy-2-Propanol Acetate	108-65-6	No data available	No data available
Ethanol	64-17-5	No data available	No data available
Isobutanol	78-83-1	No data available	No data available

Persistence and degradability: No data is available on the product itself.

Bioaccumulation potential : No data is available on the product itself.

Mobility in soil: No data is available on the product itself.

Other Adverse Environmental effects: None known or reported by the manufacturer.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal RCRA

: Dispose in accordance with all applicable regulations.

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1263	Paint	3	III	FLAMMABLE
49CFR/DOT Additional information	When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149) special provision 149.				
TDG	UN1263	Paint	3	III	FLAMMABLE
TDG Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
IMDG	UN1263	Paint	3	III	FLAMMABLE
IMDG Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
ICAO/IATA	UN1263	Paint	3	III	FLAMMABLE
ICAO/IATA Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				

Special precautions for user



SAFETY DATA SHEET

: Keep away from heat, sparks and open flame. - No smoking.
Environmental hazards : See ECOLOGICAL INFORMATION, Section 12.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance. 40	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Para-Chlorobenzotrifluoride	98-56-6	Yes	None	None.	No	N/A
1-Methoxy-2-Propanol Acetate	108-65-6	Yes	None	None	No	N/A
Ethanol	64-17-5	Yes	1 mg/L	None	No	N/A
Isobutanol	78-83-1	Yes	5000	None.	No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists			
		Listed	Type of Toxicity	CA	MA	NJ	PA
Para-Chlorobenzotrifluoride	98-56-6	No	N/Ap	No	No	Yes	No
1-Methoxy-2-Propanol Acetate	108-65-6	No	N/Ap	No	No	No	No
Ethanol	64-17-5	Yes	Cancer, birth defects or other reproductive harm	Yes	Yes	Yes	Yes
Isobutanol	78-83-1	No	N/Ap	No	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).
 WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS #	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Para-Chlorobenzotrifluoride	98-56-6	Present	Present	Present	Present	Present	Present
1-Methoxy-2-Propanol Acetate	108-65-6	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av
Ethanol	64-17-5	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av
Isobutanol	78-83-1	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av

SECTION 16. OTHER INFORMATION

Legend: ACGIH: American Conference of Governmental Industrial Hygienists AICS: Australian Inventory of Chemical Substances
 CA: California
 CAS: Chemical Abstract Services
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
 CFR: Code of Federal Regulations CSA: Canadian Standards Association DOT: Department of Transportation EC50: Effective Concentration 50%.
 EINECS: European Inventory of Existing Commercial chemical Substances ENCS: Existing and New Chemical Substances



Dampney Company, Inc.
85 Paris Street
Everett, MA, U.S.A 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 837B
SDS Preparation Date (mm/dd/yyyy): 03/20/2015

Page 7 of 7

SAFETY DATA SHEET

EPA: Environmental Protection Agency
HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods Inh: Inhalation
KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List
LC: Lethal Concentration LD: Lethal Dose
N/Av: Not Applicable N/Av: Not Available
NFPA: National Fire Protection Association NJ: New Jersey
NIOSH: National Institute of Occupational Safety and Health NOEC: No observable effect concentration
NTP: National Toxicology Program
OECD: Organisation for Economic Co-operation and Development OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances RCRA: Resource Conservation and Recovery Act
RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity TSCA: Toxic Substance Control Act TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System
Canadian Centre for Occupational Health and Safety, CCHInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).
OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015
European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer.

Preparation Date (mm/dd/yyyy): 03/20/2015

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

The information and recommendations contained herein are based on data believed to be correct. However, Dampney makes no warranty expressed or implied regarding the accuracy of these data or results to be obtained from the use thereof. Dampney assumes no responsibility for personal injury or property damage caused by use of the material described herein. It is the responsibility of the purchaser or user to ensure that this material is properly and safely used.

END OF DOCUMENT